

# PP2862

## BETAFIT Disposable Respirator Valved, FFP2 - Box 10



### Specification

- EN 149:2001 FFP2
- Comfortable Superior Fit
- Box of 10

### VF RANGE DISPOSABLE RESPIRATOR - SINGLE SHIFT USE FILTERING HALF MASK TO PROTECT AGAINST PARTICLES

#### PRODUCT DATA

##### 1. GENERAL:

1.1 Product Ref.'s **VF-2**

**VF-2V**

**VF-2CV**

1.2 Standard **EN 149:2001+A1:2009**

1.3 Classification **FFP2 NR**

##### 2. PRODUCT DESCRIPTIONS:

2.1 VF-2 Single shift use particulate respirator.

2.2 VF-2V Single shift use valved particulate respirator.

Features exhalation valve to reduce temperature and humidity within the respirator and improve exhalation resistance.

Baca Safety & Workwear, 3 Clayfield Close, Moulton Park industrial Estate,  
Northampton NN6 0AH 01604 499400

19/06/2014

2.3 VF-2CV Single shift use valved/charcoal particulate respirator.

- Features exhalation valve, [as VF-2V].
- Contains additional pre-filter loaded with activated carbon to protect against nuisance odours and organic vapours BELOW the WEL.

### **3. PROTECTION:**

3.1 For protection against non-toxic and low-to-average toxicity solid and liquid aerosols, [e.g. oil-mists], in concentrations up to 10 x WEL, [Workplace Exposure Limit].  
i.e. APF, [Assigned Protection Factor] = 10.

### **4. APPLICATIONS:**

4.1 Recommended applications include;- pharmaceutical, food processing, agriculture, ship building/repair, powdered chemicals, woodworking industry, construction, metalworking, laboratories, etc..

## **VF RANGE DISPOSABLE RESPIRATOR - SINGLE SHIFT USE FILTERING HALF MASK TO PROTECT AGAINST PARTICLES**

### **PRODUCT DATA**

#### **5. MATERIALS:**

5.1 Outer Layer: Polypropylene

5.2 Filter Media : High Filtration Efficiency Melt-Blown [Polypropylene]

5.3 Inner Layer: Polypropylene

5.4 Nosebridge: Plastic Encapsulated Iron Wire

5.5 Headstrap: Latex-Free Braided Synthetic Rubber With Polyester Yarn

5.6 Headstrap Buckle: Polypropylene

5.7 CV Pre-filter: Active Carbon With Polypropylene Substrate

[Note: VF-2CV model only]

5.8 Exhalation Valve: Valve Housing - Polypropylene

Valve Membrane - Synthetic Rubber

[Note: VF-2V & VF-2CV models only]

#### **6. DIMENSIONS:**

6.1 Respirator: Width: 114mm

Height: 163mm

6.2 Nosebridge: 90mm x 5.5mm x 1.3mm [L x W x T]

6.3 Exhalation Valve: 41mm [Diameter] x 11mm [H]

6.4 Headstrap: 700mm x 4.5mm x 1mm [L x W x T]

6.5 Headstrap Buckle: 42mm x 12mm x 2mm [In Arch Shape] [L x W x T]

#### **7. CERTIFICATION:**

These particulate respirators are EN149:2001+A1:2009 FFP2 NR certified single-use disposable respirators with CE certification according to European Council Directive 89/686/EEC and subsequent amendments.

EC-Type Examination is certified by BSI [British Standards Institution] with the CE notified body number 0086.

Baca Safety & Workwear, 3 Clayfield Close, Moulton Park industrial Estate,  
Northampton NN6 0AH 01604 499400

19/06/2014